

reisacher

VACUUM PUMPS, TRIM REMOVAL CANISTER AND COOLING UNITS

ACCESSORIES & SPARE PARTS



services

- manufacturers such as Multivac, GEA/CFS, Variovac, Sealpac, Webomatic, etc.
- Overhaul, repair and replacement service
- Available for thermoforming machines of all well-known
 Short delivery times due to high flexibility and extensive warehousing
 - · Rapid supply of spare parts

reisacher rotary vane vacuum pumps

Busch Rotary Vane Vacuum Pumps, with three-phase motor 3x 230/400 Volt + -10%, 50/60 Hz, and gas ballast valve, final pressure < 1 mbar



GPS-Article	Туре	Nom. Displacement
301139	RA 0063 F	063 cbm/h at 50 Hz / 076 cbm/h at 60 Hz
300051	RA 0100 F	100 cbm/h at 50 Hz / 120 cbm/h at 60 Hz
301140	RD 0200 A	160 cbm/h at 50 Hz / 190 cbm/h at 60 Hz
301141	RD 0300 A	250 cbm/h at 50 Hz / 300 cbm/h at 60 Hz
301131	RD 0360 A	300 cbm/h at 50 Hz / 360 cbm/h at 60 Hz



reisacher VACUUM PUMPS, TRIM REMOVAL CANISTER AND COOLING UNITS

ACCESSORIES & SPARE PARTS

reisacher

rotary vane vacuum pumps water cooled

Busch Rotary Vane Vacuum Pumps, with three-phase motor $3x\ 230/400\ Volt + -10\%$, $50/60\ Hz$, and gas ballast valve, final pressure < 1 mbar

GPS-Article	Type	Nom. Displacement
-------------	------	-------------------

301142	RD 0200 A	160 cbm/h at 50 Hz / 190 cbm/h at 60 Hz
301143	RD 0300 A	250 cbm/h at 50 Hz / 300 cbm/h at 60 Hz

reisacher roots pumps

Busch Roots Pumps, with three-phase motor, 3x 230/400 Volt + -10%, 50/60 Hz, Flange on suction- and pressure side, Hose nozzle DN 60 with O-ring



	GPS-Article	Туре	Nom. Displacement
30	1127	Panda WV 0500 C	500 cbm/h at 50 Hz / 600 cbm/h at 60 Hz
30	1163	Panda WV 1200 A	1050 cbm/h at 50Hz / 1260 cbm/h at 60Hz



reisacher

VACUUM PUMPS, TRIM REMOVAL CANISTER AND COOLING UNITS

ACCESSORIES & SPARE PARTS

reisacher trim removal canister

Trim Removal Canister, Type Phenix, 3x 208-240/360-415 Volt, 50 Hz



GPS-Article Type Nom. Displacement

301345

SR 0400 E

195 cbm/h at 50Hz / 230 cbm/h at 60Hz

reisacher cooling units

Water-Cooling-Units, Type CoolMaster, 1N220-240 Volt, 50 Hz



GPS-Article	Туре	Cooling Capacity at 15° C
301085	K-001.0	990 W
301158	K-001.7	1720 W
301159	K-003.6	3550 W
301086	K-004.9	4850 W